



4099ALU - Coated Polyester for Industrial Applications

Description

- Aluminium Coated Fabric
- Coated Polyester for Industrial Applications for Thermal Transfer, Hot Stamp, Wet Ink Printing

Recommended ink

- HS9111

Printer compatibility

- Avery Dennison Snap Series
- Avery Dennison 6x6

Features

- Premium white coated polyester for denim and overdyed applications
- Double sided product for two-side printing; reduces label size and therefore cuts material costs
- For thermal transfer printing; ultimate processing flexibility and fast data changes
- Best results are obtained with HS9111

Applications/Market

Notes

4099ALU
Coated Polyester for
Industrial
Applications



4099ALU: Technical Information

PRODUCT						
Product reference	4099ALU					
Product type	Coated Fabric					
Raw material	100% Polyester with Polyurethane Coating					
Colour	Aluminium					
Product Status	Standard Product					
PROPERTIES						
Print technology	Thermal Transfer, Hot Stamp, Wet Ink					
Front/Back print	Front/Back					
Product properties	Hand			Opacity		
	■■■□□			■■■■■		
PROCESSING/COMPATIBILITY						
Performance: the recommended combinations are based on Avery Dennison's results and experience. It is essential that all fabrics and inks are thoroughly tested prior to use through your specific processes.						
Thermal printer compatibility	<ul style="list-style-type: none"> Avery Dennison Snap Series Avery Dennison 6x6 					
Thermal transfer ribbon	Ink	Printing Quality	Domestic Wash Resistance	Dry cleaning	Overdye	Stonewash
	HS9111	■■■■■	90°C	■■■■■	Yes	Yes
Finishing	Labels can be cut with cold knife and will not fray					
CONFIGURATION						
Put up	Length	Core			<p>Core</p> <ul style="list-style-type: none"> C1 Ø 39 mm C2 Ø 76 mm C3 Ø 42 mm 	
		C1	C2	C3		
	125		•	•		
	250		•	•		
Sheets						
Width tolerance	± 1 mm					
MISCELLANEOUS						
Oeko-Tex Class	Class 1					
FMVSS	No					
Origin	Italy					
Similar Products	▲4099GRY, 4099IBT					

Products can be subject to change without notification. All information given is based on the results of testing performed by Avery Dennison. Customers should test any product thoroughly through all relevant processes.
© 2012 Avery Dennison. All rights reserved.

4099ALU-V01-201301

Information and Brand Management Division

Americas

7 Bishop Street
Framingham, MA 01702-8366
USA
Toll Free USA 800 545 9559
Int Tel +1 818 735 5000
Fax +1 818 735 6000

Europe, Middle East & Africa

Suite 24, Building 6
Hatters Lane
Croxley Green Business Park
Watford, Hertfordshire WD18 8YH
UK
Tel +44 (0) 1923 691000
Fax +44 (0) 1923 236967

South Asia

Plot No.94, Udyog Vihar Phase-I,
Gurgaon-122 016, Haryana,
India
Tel +91 124 4324 400
Fax +91 124 4324 500

Asia

32/F, Skyline Tower
39 Wang Kwong Road
Kowloon Bay, Kowloon,
Hong Kong
Tel +852 2400 4000
Fax +852 2785 1255